
anti-flooding drain DallSafe 200/1 Stone, DN 100, 200 x 200 mm

Part number: 720221
GTIN: 4001636720221
Rebate group: 3





Description:

anti-flooding drain DallSafe 200/1 Stone, DN 100, 200 x 200 mm
conforming to DIN EN 1253
for EN 13564 type 5, operation conforms to DIN 1986-100:2002-03 for use with grey waste water. Outlet DN 100 horizontal (3 degrees fall)

SPECIFICATION
– automatic rising ball
– flap-valve on outlet
– manual lock
– trap insert, 50 mm water seal (conforming to DIN EN 1253)
– tool-free removal of trap insert
– test-port
– DN 70 side inlet
– temporary blanking plate
– grating height adjustable 24 – 120 mm

MATERIAL
body polypropylene
anti-flooding drain with stainless steel grating, can be tiled individually, grating 304 stainless steel, 200 x 200 mm

Flow rates tested to DIN EN 1253:

Nominal diameter	Product standard	Min. flow rate according to norm	Water level according to norm	Flow rate at water level 20 mm	Drainage capacity
DN 100	DIN EN 1253	1.40 l/s	20.00 mm	1.59 l/s	1.59 l/s

Dallmer GmbH + Co KG · Wiebelsheidestraße 25 · 59757 Arnsberg · Tel.: +49 2932 9616-0 · Fax: +49 2932 9616-222
www.dallmer.com · info@dallmer.de
Subject to modifications due to technical development, errors and misprints