TARA Concealed thermostat with one function volume control - Brushed Durabrass (23kt Gold)

36 425 892



- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset

Brushed Durabrass (23kt Gold)	36 425 892-28
Chrome	36 425 892-00
Brushed Platinum	36 425 892-06
Platinum	36 425 892-08
Dark Chrome	36 425 892-19
Matte Black	36 425 892-33
Brushed Champagne (22kt Gold)	36 425 892-46
Champagne (22kt Gold)	36 425 892-47
Brushed Chrome	36 425 892-93
Brushed Dark Platinum	36 425 892-99

Required miscellaneous



Concealed thermostat with built-in isolators - 35 426 970 90
- max. recess depth 136 mm
- min. recess depth 80 mm

Required miscellaneous



Concealed thermostat - 35 425 970 90
- max. recess depth 136 mm
- min. recess depth 80 mm

Required miscellaneous

Drybox Concealed thermostat - 39 426 970 90

Required miscellaneous



xGRID Installation track 555 mm - 12 360 970 90

Required miscellaneous



Concealed thermostat - 35 425 970 90
- max. recess depth 136 mm
- min. recess depth 80 mm

Required miscellaneous

Drybox Concealed thermostat - 39 426 970 90


Recommended miscellaneous




xGRID Attachment set for integrating in the dry wall construction - 12 340 970 90

TARA Concealed thermostat with one function volume control - Brushed Durabrass (23kt Gold)

36 425 892
mm [inches]



Flow rate chart




Certificates

LGA_19385. LGA_19384. WRAS_1906098.

TARA Concealed thermostat with one function volume control - Brushed Durabrass (23kt Gold)

36 425 892



TARA Concealed thermostat with one function volume control - Brushed Durabrass (23kt Gold)

36 425 892

Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 90 03 166 00 90	top	1	2
2	09 12 12 053-28	base	1	20
3	04 29 06 111 01-00	spindle	1	10
4	90 23 30 023 00 90	nut	2	2
5	90 12 12 002 00 90	fixing cap	1	2
6	09 20 67 006-28	handle	1	20
7	90 17 33 022 00-28	handle	1	20
8	90 30 30 124 00 90	screw	1	2
9	90 12 12 052 00 90	base	1	2
10	09 12 12 054 90	base	1	2
11	09 28 10 187 90	regulator	1	2
12	04 29 06 024 01-00	spindle	1	10
13	09 12 12 051-28	base	1	20
14	09 31 11 134 90	pin	1	2
15	09 11 02 242-28	plate	1	20
16	09 30 30 157 90	screw	4	2
17	09 30 01 296 90	disc	1	2
18	90 30 01 190 00 90	disc	1	2
19	90 23 01 124 00 90	sleeve	2	2
20	90 18 40 077 01 90	spindle	2	2
21	09 24 04 257 90	nut	2	2
22	90 15 02 013 00 90	cartridge	1	2
23	09 28 10 188 90	regulator	1	2
24	09 28 10 189 90	regulator	1	2

We reserve the right to change designs, product range and technical specifications without prior notice.
More information can be found at: www.dornbracht.com +49 (0) 2371 8899 900 mail@dornbracht.com