Concealed thermostat with one function volume control - Dark Chrome

META

36 425 970



- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS 1906098

Dark Chrome	36 425 970-19
Chrome	36 425 970-00
Brushed Platinum	36 425 970-06
Platinum	36 425 970-08
Brushed Durabrass (23kt Gold)	36 425 970-28
Matte Black	36 425 970-33
Brushed Champagne (22kt Gold)	36 425 970-46
Champagne (22kt Gold)	36 425 970-47
Brushed Chrome	36 425 970-93
Brushed Dark Platinum	36 425 970-99

Required miscellaneous



Concealed thermostat with built-in isolators - 35 426 970 90
- max. recess depth 136 mm
- min. recess depth 80 mm

Required miscellaneous



Concealed thermostat - 35 425 970 90
- max. recess depth 136 mm
- min. recess depth 80 mm

Recommended miscellaneous



xGRID Attachment set for integrating in the dry wall construction - 12 340 970 90

Required miscellaneous




xGRID Installation track 555 mm - 12 360 970 90

Concealed thermostat with one function volume control - Dark Chrome


META

36 425 970

mm [inches]



Flow rate chart



Certificates

LGA_19385.

DVGW_DW-6512DN0119.

LGA_19384.

WRAS_1906098.

DORN BRACHT

Concealed thermostat with one function volume control - Dark Chrome

META

36 425 970

