Concealed thermostat with three function volume control - Dark Chrome

META

36 427 970



- rotary diverter with volume control and shut-off function
- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS 1906098

Dark Chrome	36 427 970-19
Chrome	36 427 970-00
Brushed Platinum	36 427 970-06
Platinum	36 427 970-08
Brushed Durabrass (23kt Gold)	36 427 970-28
Matte Black	36 427 970-33
Brushed Champagne (22kt Gold)	36 427 970-46
Champagne (22kt Gold)	36 427 970-47
Brushed Chrome	36 427 970-93
Brushed Dark Platinum	36 427 970-99

Required miscellaneous



Concealed thermostat - 35 427 970 90
- ●max. recess depth 136 mm
- ●min. recess depth 80 mm

Required miscellaneous



Concealed thermostat with built-in isolators - 35 428 970 90
- ●max. recess depth 136 mm
- ●min. recess depth 80 mm

Recommended miscellaneous



xGRID Attachment set for integrating in the dry wall construction - 12 340 970 90

Required miscellaneous




xGRID Installation track 555 mm - 12 360 970 90

Concealed thermostat with three function volume control - Dark Chrome


META

36 427 970

mm [inches]



Flow rate chart



Certificates

LGA_29330.

DVGW_DW-6512DN0119.

WRAS_1906098.

DORN BRACHT

Concealed thermostat with three function volume control - Dark Chrome

META

36 427 970

