

4. SPECIAL APPLICATIONS

4.13. Installation systems INEO

	Reference	Description
	H9201170000001	INEOLINK concealed cistern for wall-hung WC, for accessible installations, rim height +50 mm, Dual Flush, preset to 6/3 l flush, adjustable to 4,5/3 l, with insulation tank
	H8926670000001 H8926680000001	INEOLINK installation element for grip and restraint systems, for concealed cistern H920117 CH1 , left CH2 , right
	H9201180000001	INEOLINK concealed cistern for wall-hung WC, with odour extraction connection, Dual Flush, preset to 6/3 l flush, adjustable to 4,5/3 l, with insulation tank
	H9201200000001	INEOLINK concealed cistern for wall-hung WC
	H9271040000001	INEOLINK concealed cistern for wall-hung WC, under-window height 980 mm, with activation from front or from top, Dual Flush, preset to 6/3 l flush, adjustable to 4,5/3 l, with insulation tank
	H9271050000001	INEOLINK concealed cistern for wall-hung WC, under-window height 820 mm, with activation from front or from top, Dual Flush, preset to 6/3 l flush, adjustable to 4,5/3 l, with insulation tank
	H9201190000001	INEOLINK concealed cistern for wall hung WC, for corner installation, Dual Flush, preset to 6/3 l flush, adjustable to 4,5/3 l, with insulation tank